

- Simple optical multiplexing of up to 8 separate applications
- Voice, data, telemetry and CCTV can all be supported
- Any port can operate at any speed up to 10G
- Simple fibre plumbing to converge complex applications
- Long distance CWDM SFPs available
- Unpowered passive devices for highest possible reliability




MetroWAVE-8A

The MetroWAVE product range offers a series of passive CWDM and DWDM optical multiplexing functions. CWDM and DWDM multiplexing is a technique whereby different wavelengths of light are multiplexed together and transported over a singlemode fibre pair, then demultiplexed at the far end back into their original wavelengths.

The MetroWAVE product range performs these CWDM and DWDM multiplexing and demultiplexing functions passively, i.e. directly optically without using any optical-electrical-optical conversions or repeater functions. This is now the most economic approach to CWDM and DWDM multiplexing due to the widespread availability of cost effective long range vendor compatible CWDM and DWDM pluggable transceivers. The unpowered, fixed mechanical nature of these MetroWAVE products offers greater robustness and higher levels of reliability than active devices offering similar functionality.

The MetroWAVE-8A operates in the lower CWDM band (1270nm-1410nm) and can be used as a standalone CWDM multiplexer or to expand the capabilities of the MetroWAVE-9S from supporting 9 to supporting 16 CWDM applications.

Whilst the MetroWAVE product range is compatible with user exchangeable SFPs (and most other industry standard fibre transceivers), it is recommended that these are purchased from Metrodata for use in Metrodata fibre equipment to guarantee their specification and compatibility with each other.



Specifications

Optical Specification			
Parameter	Values		
	Min	Typical	Max
Operating Wavelength	1264.5nm		1417.5nm
Operating Centre Wavelength	1271/ 1291/ 1311/ 1331/ 1351/ 1371/ 1391/ 1411nm		
Passband Bandwidth	$\lambda_c \pm 6.5\text{nm}$		
Insertion Loss	Mux (TX)		2.6dB
	Demux (RX)		2.9dB
	Mux & Demux Link		3.7dB
Channel Isolation	30dB		
PDL			0.2dB
PDM			0.1ps
Directivity	50dB		
Return Loss	50dB		
Environment		Dimensions (W x L x H) mm	
Storage Temp	-40 to 85 deg C	MetroWAVE-rack	482 x 170 x 44
Operating Temp	-5 to 75 deg C	MetroWAVE-8A	142 x 170 x 39
Humidity	95% RH, non-condensing	Power Supply	
Pressure	86 - 106 kPa	Power Consumption	Unpowered
Compliance & Approvals			
Safety	EN60950		
EMC	EN55032		

Order Codes

Product	Part Number
MetroWAVE-8A	80-32-021
MetroWAVE-rack (3 units)	80-32-051

For more data on Metrodata products, visit our website at www.metrodata.co.uk
 Metrodata reserves the right to change specifications without notice.
 Please check when ordering.